

## SCHEDA TECNICA

# MERINGA

Tit. 3800 85% Cotone ( CO ) – 15 %Poliestere Metallizzato ( PL)

Impiego: Macchina rettilinea finezza 5 ad un capo

Colori: Cartella realizzata con effetti bi colori

### Istruzioni di lavaggio:

Si consiglia di lavare a secco con il solvente indicato. In caso di lavaggio ad acqua usare una temperatura massima di 30°C con saponi neutri non ammorbidenti. Per maglieria rigata con tinte forti lavare soltanto a secco.

TRATTAMENTO del telo in cartella : Lavaggio in acqua 30 secondi a 20°

con 120 millilitri di ammorbidente ( tipo SEBOSAN SX a New ) ASCIUGATURA in "tumbler" a 60°

### Avvertenze:

- a) Essendo un filato fantasia deve essere tollerato uno scarto medio del 4 % - 5 % per imperfezioni tintoriali e di struttura.  
b) E' consigliabile lavorare a 2 o più guida fili.

### Etichettatura:

per maglia UNITA:



per maglia RIGATA:



### Importante:

In caso di **ri-paraffinatura** del filato utilizzare bassa velocità per ottenere rocche morbide e soprattutto di densità uniforme. All'inizio della lavorazione **controllare** attentamente i primi teli ed in caso di irregolarità del prodotto avvertire immediatamente l'**ufficio tecnico** di FILOBEL per l'eventuale sostituzione

In ogni caso la filatura non può riconoscere danni sul prodotto già lavorato.

# MERINGA

Count 3800 85% Cotone ( CO ) – 15%Polyester Metall ( PL)

Use: yarn to be used at one end on 5 gage flat-knitting machine.

Colours: colour card realized with effect be -colour.

### Washing Instructions:

Dry clean with suitable solvent. Wash in water with mild non-conditioning soap at a maximum temperature of 30°C. In the case of striped Knitwear in bright colours, dry clean only.

### Warnings:

- a) Being a fancy yarn an average of 4% -5 % tolerance must be accepted for dyeing and structural faults  
b) It is very important to work with 2 or more thread guides.

### Labelling:

For SOLID knits:



For STRIPED knits:



### Important:

In the event of yarn **re-waxing**, use a low speed to obtain soft cones and above all uniform density. Please **check** carefully the first knitted fabrics and in case of unevenness, immediately notify the **FILOBEL technical department** who will authorise any replacement. In any case, the spinning company cannot accept responsibility for damage on knitted panels.