

SCHEDA TECNICA

SESAMO

Tit. 2000 90% Cotone (CO) – 10% Poliestere Metallizzato (PL)

Impiego: Macchina rettilinea finezza 3 ad un capo.

Colori: Cartella realizzata con due nodini di colore diverso.

Istruzioni di lavaggio:

Si consiglia di lavare a secco con il solvente indicato. In caso di lavaggio ad acqua usare una temperatura massima di 30°C e saponi Neutri non ammorbidenti. Per maglieria rigata con tinte forti lavare a secco.

Avvertenze:

- Evitare l'asciugatura in centrifuga. Asciugare su piano orizzontale. Non torcere il capo.
- E' indispensabile lavorare a 2 o più guida fili.
- Essendo un filato fantasia deve essere tollerato uno scarto medio del 4% - 5 % per imperfezioni tintoriali e di struttura.

.Etichettatura:
per maglia UNITA:



per maglia RIGATA:



Importante:

In caso di ri - paraffinatura del filato utilizzare bassa velocità per ottenere rocche morbide e soprattutto di densità uniforme. All'inizio della lavorazione **controllare** attentamente i primi teli ed in caso di irregolarità del prodotto avvertire immediatamente l'ufficio tecnico di FILOBEL per l'eventuale sostituzione.

In ogni caso la filatura non può riconoscere danni sul prodotto già lavorato.

SESAMO

Count 2000 90% Cotton (CO) – 10% Polyester Metal (PL)

Use: yarn to be used at one end on 3 gg flat-knitting machine.

Colours: Colour card realised with two little knot of different colour


Washing Instructions:

We advise of washing with water, the temperature must not exceed 30°C and non-softening neutral soaps must be used. Bright-coloured striped knitwear should be dry-cleaned

Warnings:

- Do not spin dry. Dry on a flat surface. Do not twist the garment.
- It is necessary to work with 2 or more thread guides.
- Being a fancy yarn an average of 4 % - 5 % tolerance must be accepted for dyeing and structural faults

Labelling:
For SOLID knits:



For STRIPED knits:



Important:

In the event of yarn re-waxing, use a low speed to obtain soft cones and above all uniform density. Please check carefully the first knitted fabrics and in case of unevenness, immediately notify the FILOBEL technical department who will authorise any replacement.

In any case, the spinning company cannot accept responsibility for damage on knitted panels.